

DEUTA

Indicating Units





Table of contents

DEUTA indicating units	5
Product highlights	6
ENG 6, 8/9, 10/9, 13/9	8
EZG 10/9, EZG 13/9	10
EQG 9/9, EQG 14/9	12
EGS 3/9 a, EGS 3/9 az	14
EGS 5/9	16
EGS 10/9, EGS 6	18



»DEUTA indicator units

Product highlights at a glance!«

Forward-looking technology

Everything from one source

Consultation, development, layout and selection of components, fitting, testing and production: DEUTA controls the entire process chain from production to qualification and worldwide support.

Platform concept

Three platforms, many possibilities for individualisation. With just a few components and plug connections, we have indicating units compatible in terms of installation and function available at any time.

Longevity

High-quality components and processes lead to high MTBF values and low life-cycle costs.

Obsolescence management

Follow-up concepts are already considered during the design phase. This ensures the availability of the indicating units across the entire life cycle. New indicating units are compatible to the predecessors in form, fitting accuracy and function.

- **Holistic:** Deuta controls the entire process chain for your individual indicating units.
- **Flexible:** Three technologies for indicating units: Stepper motor, moving coil instrument, digital indicator
- **Compatible:** Form-fit-function
- **Rugged:** Regarding extreme environmental conditions
- **High:** The MTBF values

Economic efficiency

Modular concept

Longevity

Obsolescence management

Product Overview



ENG 6, 8/9, 10/9, 13/9

- Controlled either with voltage, currents or PWM signal
- Device versions available either with LED lighting or lamp bulb



EZG10/9, EZG13/9

- with summation counter
- Controlled either with voltage, currents or PWM signal
- Device versions available either with LED lighting or lamp bulb



EQG 9/9, EQG 14/9

- Controlled either with voltage, currents or PWM signal
- Device versions available either with LED lighting or lamp bulb



EGS 3/9 a, EGS 3/9 az

- Controlled either with voltage, currents or PWM signal
- Device versions available either with LED lighting or lamp bulb



EGS 5/9

- Controlled either with voltage, currents or PWM signal
- Device versions available either with LED lighting or lamp bulb



EGS 10/9, EGS 6

- Controlled either with voltage, currents or PWM signal
- Device versions available either with LED lighting or lamp bulb



»DEUTA analogue panel meters -
ENG indicating units - a round affair for more safety!«

Flexible control

The round indicating units **ENG 6** to **ENG 13** can be controlled either with voltages (AC, DC), currents (DC) or a PWM signal. Devices with current input can also be controlled with 4-20 mA.

Choice

Indicating units with 4...20 mA current input each have a “mechanical” and an “electrical” zero point (life zero). They are available either with flat connectors or D-Sub.

ENG 6, ENG 8/9, ENG 10/9, ENG13/9

- Controlled either with voltage, currents or PWM signal
- Device versions available either with LED lighting or lamp bulb

ENG 6 ENG 8/9 ENG 10/9 ENG13/9

Feature/Specification	
Panel cutout	ENG 6: Ø 61 ^{+0.5} mm ENG 8/9: Ø 81 ^{+0.5} mm ENG 10/9: Ø 101 ^{+0.5} mm ENG 13/9: Ø 131 ^{+0.5} mm
Installation depth	ENG 6: approx. 80 mm ENG 8/9: approx. 90 mm ENG 10/9: approx. 90 mm ENG 13/9: approx. 90 mm
Weight	ENG 6: approx. 0.3 kg ENG 8/9: approx. 0.5 kg ENG 10/9: approx. 0.6 kg ENG 13/9: approx. 0.8 kg
Mounting	Clamping yoke / clamp
Installation position	0-90-180°
Degree of protection front face	IP53
Degree of protection plug	IP40
Connection	6.3 x 0.8 DIN 46244 / D-Sub
Internal scale illumination	LED
External scale illumination	For devices without internal lighting possible via light slits
Input signals	AC, DC, PWM
Data for moving coil device	e.g. 20 mA, 1.5 mA ¹⁾
Load resistance	< 20 ohm at 20 mA meas.res.
Pointer deflection	240°
Accuracy class	ENG 6: 1,5 ENG 8/9, ENG 10/9, ENG13/9: 1,5; 1 ²⁾
Temperature range	-25°C to +70°C
Test voltage	1000 V _{eff} , 50 Hz, 1 min
Vibration testing	EN61373 cat1, class: B
Device definition	EN60051, EN50155
Conformity	CE
Housing	Sheet steel
Additional indicator	Individual versions with mileage recorder

¹⁾ others upon request
²⁾ at extra charge



ENG 6



ENG 8/9



ENG 10/9



ENG 13/9



»DEUTA analogue panel meters –
EZG indicating units - with summation counter!«

Flexible control
Models EZG 10/9 and EZG 13/9 are identical in structure and function to indicators ENG 10/9 and EZG 13/9 but incorporate an additional mechanical 7-digit summation counter.

- EZG10/9 6, EZG13/9**
 - with summation counter
 - Controlled either with voltage, currents or PWM signal
 - Device versions available either with LED lighting or lamp bulb

EZG10/9 EZG13/9

Feature/Specification	
Panel cutout	EZG 10/9: Ø 101+0,5 mm EZG 13/9: Ø 131+0,5 mm
Installation depth	EZG 10/9: approx. 90 mm EZG 13/9: approx. 90 mm
Weight	EZG 10/9: approx. 0.6 kg EZG 13/9: approx. 0.8 kg
Mounting	Clamping yoke / clamp
Installation position	0-90-180°
Degree of protection front face	IP53
Degree of protection plug	IP40
Connection	6.3 x 0.8 DIN 46244 / D-Sub
Internal scale illumination	LED
External scale illumination	For devices without internal lighting possible via light slits
Input signals	AC, DC, PWM
Data for moving coil device	e.g. 20 mA, 1.5 mA ¹⁾
Load resistance	< 20 ohm at 20 mA meas.res.
Pointer deflection	240°
Accuracy class	1.5; 1 ²⁾
Temperature range	-25°C to +70°C
Test voltage	1000 V _{eff} 50 Hz, 1 min
Vibration testing	EN61373 cat:1, class: B
Device definition	EN60051, EN50155
Conformity	CE
Housing	Sheet steel
Additional indicator	Individual versions with mileage recorder

¹⁾ others upon request
²⁾ at extra charge



EZG 10/9



EZG 13/9



»DEUTA analogue panel meters –
EQG indicating units - square and good!«

Durable
The EQG../9 indicating units have a square housing.
They have the same features as the ENG series.
A long-life LED lighting is integrated in the housings.

They are available in versions with flat connectors or
with D-Sub.

- EQG 9/9, EQG 14/9
- Controlled either with voltage, currents or PWM signal
 - Device versions available either with LED lighting or lamp bulb

EQG 9/9 EQG 14/9

Feature/Specification	
Panel cutout	EQG 9/9: 92 x 92 ^{+0,8} mm EQG 14/9: 138 x 138 ⁺¹ mm
Installation depth	approx. 90 mm
Weight	EQG 9/9: approx. 0.6 kg EQG 14/9: approx. 0.8 kg
Mounting	Tensioning elements at the housing
Installation position	0- 90-180°
Degree of protection front face	IP53
Degree of protection plug	IP40
Connection	6.3 x 0.8 DIN 46244 / D-Sub
Internal scale illumination	with LED
External scale illumination	-
Input signals	AC, DC, PWM
Data for measuring device	e.g. 20 mA, 1.5 mA ¹⁾
Load resistance	< 20 ohm at 20 mA meas.res.
Pointer deflection	240°
Accuracy class	1.5
Temperature range	-25°C bis +70°C
Test voltage	1000 V _{eff} 50 Hz, 1 min
Vibration testing	EN61373, cat: 1, class: B
Device definition	EN60051, EN50155
Conformity	CE
Housing	Aluminium

¹⁾ others upon request



EQG 9/9



EQG 14/9



»DEUTA analogue panel meters -
Double indicating units EGS -
independent indicating units for reference and actual values«

Doubly safe

The indicating units have two independently operating moving coil instruments whose inputs can be adapted to current, voltage (AC/DC) or PWM signals.

Versions with current inputs of 4-20 mA make make it easier to recognise malfunctions thanks to the mechanical and electrical zero point. The pointer will be below the zero position in case of errors in the current loop.

GS 3/9 a, EGS 3/9 az

- Controlled either with voltage, currents or PWM signal
- Device versions available either with LED lighting or lamp bulb

EGS 3/9 a EGS 3/9 az

Feature/Specification	
Panel cutout	Ø 131 ^{+0,5} mm
Installation depth	approx. 110 mm
Weight	approx. 1 kg
Mounting	Clamp
Installation position	0-90-180°
Degree of protection front	IP53
Degree of protection plug	IP40
Connection	6.3 x 0.8 DIN 46224
Internal scale illumination	2 x 2W Ba7s
External scale illumination	through light slits
Input signal	AC, DC
Data for measuring device	e.g. 20 mA, 1.5 mA ¹⁾
Load resistance	< 20 ohm at 20 mA meas.res.
Pointer deflection	240°
Accuracy class	1.5, 1 ²⁾
Temperature range	-25°C bis +70°C
Test voltage	1000 V _{eff} , 50 Hz, 1 min
Vibration testing	EN61373, cat: 1, class: B
Device definition	EN60051, EN50155
Conformity	CE
Housing	Sheet steel
Additional indicator	EGS 3/9 az: Counter 7-digit
Supply	EGS 3/9 az: Counter 24 V DC ± 30 %, P = 250 mW
Input signal	EGS 3/9 az: f _{max} 12 Hz, pulse dur. min. 20ms

¹⁾ others upon request
²⁾ at extra charge



EGS 3/9 a



EGS 3/9 az



»DEUTA analogue panel meters -
Double indicating units EGS -
independent indicating units for reference and actual values«

Doubly safe
EGS 3/9 indicating units have two independently
operating moving coil instruments whose inputs can be
adapted to current, voltage (AC/DC) or PWM signals.

- EGS 5/9**
- Controlled either with voltage, currents or PWM signal
 - Device versions available either with LED lighting or lamp bulb

EGS 5/9

Feature / Specification	
Panel cutout	Ø 101 ^{+0,5} mm
Installation depth	approx. 98 mm
Weight	approx. 1 kg
Mounting	Clamp
Installation position	0-90-180°
Degree of protection front	IP53
Degree of protection plug	IP40
Connection	6.3 x 0.8 DIN 46244
Internal scale illumination	with LED
External scale illumination	through light slits
Input signal	AC, DC, PWM
Data for moving coil device	0-20 mA, 1.5 mA ¹⁾
Load resistance	< 20 ohm at 20 mA meas.res.
Pointer deflection	240°
Accuracy class	1.5, 1 ²⁾
Temperature range	-25°C bis +70°C
Test voltage	1000 V _{eff} , 50 Hz, 1 min
Vibration testing	EN61373, cat: 1, class: B
Device definition	EN60051, EN50155
Conformity	CE
Housing	Sheet steel

¹⁾ others upon request
²⁾ at extra charge



EGS 5/9



»DEUTA analogue panel meters - Double indicating unit EGS - doubly safe«

Doubly safe

The indicating units have two independently operating moving coil instruments whose inputs can be adapted to current, voltage (AC/DC) or PWM signals.

Versions with current inputs of 4-20 mA make it easier to recognise malfunctions thanks to the mechanical and electrical zero point. The pointer will be below the zero position in case of errors in the current loop.

Traction and voltage values

EGS 6 indicating units with a customer-specific RS485 - protocol and LED lighting.

The microcontroller is monitored with a reset module. The power is supplied through a galvanically isolated DC/DC converter.

EGS 10/9, EGS 6

- Controlled either with voltage, currents or PWM signal
- Device versions available either with LED lighting or lamp bulb

EGS 10/9 EGS 6

Feature/Specification	
Panel cutout	EGS 10/9: Ø 92 ^{+0,8} x 92 ^{+0,8} mm EGS 6: Ø 185 ⁺¹ x 92 ⁺¹ mm
Installation depth	EGS 10/9: approx. 108 mm EGS 6: approx. 100 mm
Weight	EGS 10/9: approx. 1 kg EGS 6: approx. 0.8 kg
Mounting	EGS 10/9: Tensioning element at the housing EGS 6: V-clamp
Installation position	EGS 10/9: 0-90-180° EGS 6: 0-90-160°
Degree of protection front	EGS 10/9: EGS 6: IP 53
Degree of protection plug	IP40
Connection	EGS 10/9: 6.3 x 0.8 DIN 46224 EGS 6: Push-on terminal strip 10-pole, + D-Sub9
Internal scale illumination	with LED
Input signal	EGS 10/9: AC, DC, PWM EGS 6: RS 485 - Telegram
Data for moving coil device	EGS 10/9: 0-20 mA, 1.5 mA ¹⁾ EGS 6: 1.5 mA
Load resistance	< 20 Ohm bei 20mA Messw.
Pointer deflection	240°
Accuracy class	1.5
Temperature range	-25°C bis +70°C
Test voltage	1000 V _{eff} , 50 Hz, 1 min
Vibration testing	EN61373, cat. 1, class: B
Device definition	EN60051, EN50155
Conformity	CE
Housing	EGS 10/9: Aluminium EGS 6: Plastic, fibre reinforced

¹⁾ others upon request



EGS 10/9



EGS 6

DEUTA-WERKE

Paffrather Straße 140 | 51465 Bergisch Gladbach | Germany
Phone +49 (0) 2202 958-100 | Fax +49 (0) 22 02 958-145
support@deuta.de | www.deuta.com | www.icontrust.com



DEUTA-WERKE GmbH | Paffrather Str. 140 | 51465 Bergisch Gladbach | Germany | Phone +49 (0) 2202 958-100 | Fax +49 (0) 22 02 958-145 | E-Mail: support@deuta.de | www.deuta.com
Represented by the Managing Directors: Mr. Dr. Rudolf Ganz and Mr. Thomas Blau | Register court: Amtsgericht Köln, Register number: HRB Köln 67 107 | Value added tax identification number: DE 265417448 | Pictures and articles including any other contents printed in the brochure are proprietary. The reprint, copy, distribution as well as any other actions violating the copyright are subject to prior written authorization by DEUTA-WERKE GmbH.

The information contained in this brochure are of general information purposes only representing examples of our standard products. The information contained in the brochure does not constitute any guarantee for technical data or features. DEUTA-WERKE GmbH checked the information carefully, however, it assumes no liability for the timeliness, correctness and completeness or quality of the provided information. Required special features are subject to separate individual agreement on the purchase of a product. Only variations of the pictured standard products agreed on the purchase are decisive.

The state of products pictured and described in this brochure corresponds with that on the final editing, however, DEUTA-WERKE GmbH reserves the right to make changes in the meantime. The names DEUTA REDBOX®, IconTrust®, SelectTrust®, SignalTrust®, MouseTrust® und DEUTA SmartView® are registered trademarks of DEUTA-WERKE GmbH. IconTrust® and SelectTrust® are patented inventions owned by DEUTA-WERKE GmbH. Without prior written consent of DEUTA-WERKE GmbH the use of trademarks and patents is not allowed.